

BRADYPRINTER™

Models 1244 and 1344



Printers are available in either 203 dpi or 300 dpi print resolution.



Models 1244 and 1344 are available with optional media stand.

The BRADYPRINTER™ models 1244 and 1344 are small, compact and economical. Featuring print resolutions of either 203 dpi or 300 dpi and a wide print width of 104 mm, the 1244 and 1344 printers are ideal for general purpose product identification, wire and cable marking and laboratory identification.

For small to medium volume printing, the BRADYPRINTER™ models 1244 and 1344 provide all the power and quality you need for on-demand in-house printing. The moveable transmissive sensor allows the use of all BRADY stock configurations in a variety of materials including polyester, paper, vinyl and sleeves.

BRADYPRINTER™ Model 1244

| Reference | Description |
|-----------|------------------|
| BP-1244 | BRADY Model 1244 |

BRADYPRINTER™ Model 1244 specifications

| | |
|----------------------|---|
| Print resolution | 203 dpi |
| Print speeds | Selectable print speeds at 25.6 mm increments from 50.80 mm to 101.60 mm per second |
| Minimum label length | 6.35 mm |

BRADYPRINTER™ Model 1344

| Reference | Description |
|-----------|------------------|
| BP-1344 | BRADY Model 1344 |

BRADYPRINTER™ Model 1344 specifications

| | |
|----------------------|---|
| Print resolution | 300 dpi |
| Print speeds | Selectable print speeds at 25.6 mm increments from 50.80 mm to 101.60 mm per second |
| Minimum label length | 6.35 mm |

BRADYPRINTER™ Models 1244 & 1344 Field-Installable Options

| Reference | Description |
|--------------------|------------------------------------|
| BP-12/13-3MB-FLASH | 1244/1344 3MB memory expansion |
| BP-12/13-REALCLOCK | 1244/1344 internal clock option |
| BP-12/13-CUTTER | 1244/1344 standard cutter option |
| BP-12/13-LD-CUTTER | 1244/1344 light duty cutter option |
| BP-12/13-KEYBOARD | 1244/1344 keyboard |
| BP-12/13-MS | 1244/1344 media stand |
| BP-12/13-PRESSENSR | 1244/1344 present sensor option |

BRADYPRINTER™

Models 1244 and 1344

CONTINUED

Ribbons

- ▶ 110 m length
- ▶ Recommended to be as wide as media
- ▶ 12.7 mm core

Programming Language

- ▶ DLP language programming

Fonts (standard)

- ▶ Bitmap fonts A through H and GS symbols
- ▶ Scalable font CG Triumvirate™ Bold Condensed (4 pts.-36pts.)
- ▶ IBM® Code Page 850 multilingual character set

Electrical

- ▶ Universal power supply with power-factor correction 90-264 VAC, 48-62 Hz

Electronics

- ▶ 32-bit microprocessor
- ▶ 2 MB RAM memory
- ▶ 1 MB flash

Bar Codes/ Symbologies

- ▶ All popular symbologies including:
Linear bar codes: Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2 or 5 digit extensions, Plessey, Postnet, Standard 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, LOGMARS, MSI, Codabar
2-dimensional bar codes: Codablock, PDF-417, Code 49, DataMatrix, Maxi Code, Micro-PDF, QR Code

Physical

- ▶ Height: 152.42 mm
- ▶ Width: 215.90 mm
- ▶ Depth: 241.30 mm
- ▶ Weight without options: 2.4 kg printer only

Communications Interfaces

- ▶ Serial RS232 9 pins interface standard
- ▶ High speed parallel interfaces, Centronics® compatible

Environment

- ▶ Operating temperature: 5° to 35°C
- ▶ Storage/Transportation: -40° to 60°C
- ▶ 20% to 85% Non-condensing R.H.

Options

- ▶ Cutter
- ▶ External Media Supply
- ▶ External keyboard
- ▶ Real time clock board
- ▶ Present sensor (peel off)
- ▶ Additional battery pack



Identification Solutions
& Specialty Tapes

Belgium : 32 (0) 52 457 811
France : 33 (0) 1 69 29 67 00
Germany : 49 (0) 6103 7598-0
Italy : 39 (0) 2 9670 0507
Sweden : 46 (0) 8 590 057 30
United Kingdom : 44 (0) 1295 228200

www.bradyeurope.com

Your BRADY distributor

LEXICRAFT
NAMEPLATES LABELS SIGNS

50 Cleveland Street,
Birkenhead, Wirral. CH41 6LG.
Tel: +44 (0) 151 647 9281
Fax: +44 (0) 151 666 1079

e-Mail: sales@lexicraft.co.uk
Web: www.lexicraft.co.uk